



| Artikel-Nr. | Wmax ¹⁾ (J) | F ¹⁾ (kN) | f ¹⁾ (mm) | Gewicht (kg) | d ₁ (mm) | h (mm) | d ₂ | t (mm) | R (mm) | s (mm) |
|-------------|---------------------------|-------------------------|-------------------------|-----------------|------------------------|-----------|----------------|-----------|-----------|-----------|
| GI-040x032 | 70 | 15 | 18 | 0,15 | 40 | 32 | M8 | 8 | 3 | 2 |
| GI-050x040 | 140 | 24 | 22 | 0,25 | 50 | 40 | M10 | 10 | 10 | 2 |
| GI-063x050 | 280 | 37,5 | 28 | 0,3 | 63 | 50 | M10 | 10 | 12,5 | 3 |
| GI-080x063 | 560 | 60 | 35 | 0,6 | 80 | 63 | M12 | 12 | 16 | 3 |
| GI-100x080 | 1120 | 95 | 44 | 1,0 | 100 | 80 | M12 | 12 | 20 | 4 |
| GI-125x100 | 2240 | 150 | 55 | 1,7 | 125 | 100 | M16 | 16 | 25 | 4 |
| GI-160x125 | 4400 | 240 | 69 | 3,8 | 160 | 125 | M16 | 16 | 32 | 6 |
| GI-200x160 | 8800 | 375 | 88 | 7,9 | 200 | 160 | M20 | 18 | 40 | 6 |
| GI-250x200 | 12800 | 400 | 110 | 15,9 | 250 | 200 | M20 | 18 | 50 | 8 |
| GI-315x250 | 25000 | 640 | 137 | 31,8 | 315 | 250 | M24 | 22 | 80 | 8 |

(1J = 1Nm = 0,102mkp)

¹⁾ Werte für $v < 1\text{m/s}$ und Federweg $f = 0,55 \times h$
 Gummiwerkstoff: NR 70° Shore A
 Metallteile: Stahl verzinkt