



Artikel-Nr.	Wmax ¹⁾ (J)	F ¹⁾ (kN)	f ¹⁾ (mm)	Gewicht (kg)	d ¹ (mm)	h ¹ (mm)	a (mm)	d ² (mm)	e (mm)	s (mm)
ZFK-080x040	200		30	0,40		40				
ZFK-080x080	400	40	60	0,60	80	80	110	13	80	10
ZFK-080x120	600		90	0,70		120				
ZFK-100x050	400		38	0,60		50				
ZFK-100x100	800	63	75	0,90	100	100	125	13	100	10
ZFK-100x150	1200		112	1,15		150				
ZFK-125x063	750		47	1,20		63				
ZFK-125x125	1500	100	94	1,65	125	125	160	17	125	12
ZFK-125x190	2200		142	2,25		190				
ZFK-160x080	1600		60	2,20		80				
ZFK-160x160	3200	160	120	3,10	160	160	200	17	160	12
ZFK-160x240	4800		180	4,00		240				
ZFK-200x100	3150		75	4,00		100				
ZFK-200x200	6300	250	150	5,80	200	200	250	21	200	14
ZFK-200x300	9450		225	7,50		300				

(1J = 1Nm = 0,102mkp)

Grundplatte auch in Aluminium lieferbar.
 Zellkörper-Werkstoff: zelliges Polyurethan-Elastomer (0,53g/cm³)
 Ab ø 200 mm mit Seilsicherung lieferbar