



Artikel-Nr.	Wmax ¹⁾ (J)	F ¹⁾ (kN)	f ¹⁾ (mm)	Gewicht (kg)	d ₁ (mm)	h ₁ (mm)	a (mm)	d ₂ (mm)	e (mm)	s (mm)
ZFS-250x125	6000		94	7,50		125				
ZFS-250x250	12000	400	188	11,00	250	250	315	21	250	15
ZFS-250x375	18000		280	15,00		375				
ZFS-315x160	12000		120	26,00		160				
ZFS-315x315	24000	630	236	33,00	315	315	400	21	315	15
ZFS-315x475	36000		356	41,00		475				
ZFS-400x200	24000		150	51,00		200				
ZFS-400x400	48000	1000	300	66,00	400	400	500	25	400	20
ZFS-400x600	72000		450	81,00		600				
ZFS-500x250	48000		188	88,00		250				
ZFS-500x500	96000	1600	375	116,00	500	500	600	25	500	20
ZFS-500x750	144000		563	146,00		750				
ZFS-600x300	63000		225	129,00		300				
ZFS-600x600	125000	2000	450	178,00	600	600	730	25	600	20
ZFS-600x900	188000		675	230,00		900				

(1J = 1Nm = 0,102mkp)

Zellkörper-Werkstoff: zelliges Polyurethan-Elastomer (0,53g/cm³)
Auch mit Seilsicherung lieferbar